

## Crate Washer



### Features

- Automatically start wash and rinse with energy saving infrared sensor control system
- Imported brand wash pump motor 2 IP56/2.2kW comply with SUS304 stainless steel pump body and impeller
- Double water jet design reaches 10~15kg washing pressure. The lower water arm has angle cutting to make the objects cleaner.
- Double rinse systems with 360° surround rinse, reducing rinse usage effectively.
- High efficient double air blade system, get rid of 90% of water.
- Detergent saving system, rinse water directly lead to wash tank, reduce consumption of detergent
- Double layer door and body to prevent heat loss, energy saving and reduce noise
- Whole machine is made of SUS304 stainless steel for durability, compliance with hygiene and anti-rot
- CE Certification + ISO 9001

## Crate Washer

	VT-L3R(H)CD2-E	VT-L3R(H)CD2-S
Model	VT-L3R(H)CD2-E	VT-L3R(H)CD2-S
Flight Type	3 Tank + Air Blade + 2 Dryer	3 Tank + Air Blade + 2 Dryer
Dimension	8950 x 1175/1814 x 2167mm	8950 x 1175/1814 x 2167mm
Loading Dimension	720*420mm	720*420mm
Capacity	3.0~5.0m/min	3.0~5.0m/min
Rinse Usage	700L/Hr	700L/Hr
Wash Pump Power	2.2~4.0kW	2.2~4.0kW
Wash Tank Heater	15kW	17kg/Hr
Booster Heater	45kW	52kg/Hr
Rinse Pump Power	0.25kW	0.25kW
Conveyor Motor	0.75kW~1.5kW	0.75kW~1.5kW
Inlet / Outlets	¾" / Φ50mm	¾" / Φ50mm
Steam Pipe		1.5" / After decompression ¾"
Steam Pressure		After decompression 3~5kg
Air Blade Motor Power	4kW + 4kW	4kW + 4kW
Power/Steam Supply	400V/50Hz/3ph	160kg/Hr
Electrical/Steam Loading	135kW	20kW
Dryer(Optional)		L: 800mm H: 2150mm Motor Power: 1.5kW Heater: 12kW Total Electrical Loading: 13.5kw (Steam: 26kg/h)
Water Jet(Optional)		L: 400mm H: 1245mm Motor Power: 4kw Water Jet create pressure 10kg and above
Heat Recovery System(Optional)		

